
全产品系列简介

Full Line Product Overview

Industrial Motors and Systems



通用用途马达
特定用途马达
暖通空调马达
特殊用途产品

GENERAL PURPOSE MOTORS
DEFINITE PURPOSE MOTORS
HVAC MOTORS
SPECIAL PURPOSE PRODUCTS



eBusiness Solutions

State-of-the-art eBusiness systems that offer real-time solutions. Whether you need to check stock availability or need detailed specifications, you can access online information anytime, anywhere.

MOTORBOSS® Product Information Resource

24/7, 365 days a year availability. This easy-to-use system provides you real-time answers quickly. For more information, go to www.motorboss.com.

eCatalog

Using eCatalog makes it easier and faster than ever to find the right motor to meet your needs. eCatalog provides details on all U.S. Motors® brand stock motor ratings. For more information, go to www.usmotors.com/default_ecatalog.htm.

On-line Motor Cross Reference Library

Having trouble finding a replacement motor for an OEM, competitor model or catalog number? The online cross reference tool has more than 50,000 cross references to some of the most popular part numbers. Log on today to find a replacement motor at www.usmotors.com/default_ecatalog.htm.

MOTROPRO® Training

MOTROPRO® is a self-paced, interactive online electric motor training tool. After you complete MOTROPRO training, we will send you a certificate of completion. Sign on today at www.usmotors.com/motorpro to become a motor professional!

eBusiness Solutions

先进的eBusiness系统提供了实时的解决方案。您可以随时随地在线查询产品在库情况或是您所需要的详细规格。

MOTORBOSS® 产品信息库

全365天, 24小时可用。这个易于使用的系统向您提供快速, 实时的解答。更多的详细信息, 请访问 www.motorboss.com。

eCatalog 产品目录

使用eCatalog产品目录查询系统能更快更容易的让您找到适合需要的马达。eCatalog提供全部U.S. Motor品牌的马达在库产品的详细额定值。更多信息, 请访问 www.usmotors.com/default_ecatalog.htm

在线交互查询式参考资料库

您是否在寻找OME制造商的替换产品, 或是竞争对手的型号, 或是产品编号时感到困难? 在线交互式参考资料库拥有超过5万的最常用部品编号的资料。请登录www.usmotors.com/default_ecatalog.htm 查询替代马达。

MOTROPRO® 培训课程

MOTROPRO®是一个自我管理进度的, 在线互动式的马达培训电子工具。当您完成MOTROPRO培训后, 我们将把完成证书寄给您。请登录www.usmotors.com/motorpro成为马达专家!

通用用途工业马达 General Purpose Industrial Motors

三相,全闭外扇型,室外用

- 1 HP~350 HP
- 3600,1800,1200,900 RPM
- 机座尺寸:143~449
- 节能型,NEMA Premium高效节能型
- 铸铁机壳及机盖
- 可选滚珠及滚柱轴承

Three Phase, TEFC, Hostile Duty

- 1 HP through 350 HP
- 3600, 1800, 1200 and 900 RPM
- 143 through 449 frame
- Energy and NEMA Premium[®]† efficient
- Cast iron frame and brackets
- Ball and roller bearing options



三相,全闭外扇型,CORRO-DUTY[®]系列,防腐型

- 1 HP~400 HP
- 3600,1800,1200 RPM
- 机座尺寸:143~447
- 全铸铁构造
- NEMA Premium高效节能

Three Phase, TEFC, CORRO-DUTY[®]

- 1 HP through 400 HP
- 3600, 1800 and 1200 RPM
- 143 through 447 frame
- All cast iron construction
- NEMA Premium[®]† efficient



三相,全闭外扇型,841 PLUS[®]系列

- 1 HP~400 HP
- 3600,1800,1200 RPM
- 机座尺寸:143~447
- 采用Inpro/Seal[®]的VBXX[®]轴承支架帮助保护轴承
- 符合IEEE841GM7E-TA[®]规格
- 5年产品限定保证
- NEMA Premium高效节能

Three Phase, TEFC, 841 Plus[®]

- 1 HP through 400 HP
- 3600, 1800 and 1200 RPM
- 143 through 447 frame
- VBXX[®]† bearing isolators by Inpro/Seal[®]† helps protect bearings
- Meets IEEE[®]† 841 GM7E-TA specifications
- Five-year limited warranty*
- NEMA Premium[®]† efficient



危险场所用

- 单相及三相,全闭外扇型
- 1/4 HP~150 HP
- 3600,1800,1200,900 RPM
- 机座尺寸:56~445
- 节能型及高效节能型
- Class I Group D;
- Class I, Groups C and D,
- 和Class II, Groups E, F 及G

Hazardous Location

- Single and three phase, TEFC
- 1/4 HP through 150 HP
- 3600, 1800, 1200 and 900 RPM
- 56 through 445 frame
- Energy and premium efficient
- Class I Group D; Class I, Groups C and D, and Class II, Groups E, F, and G



三相,全闭外扇型,UNIMOUNT[®]系列

- 1/4 HP~30 HP
- 3600,1800,1200, 900 RPM
- 机座尺寸:56~286
- 节能型, NEMA Premium高效节能型
- C-Face机盖、带安装脚或不带,
- 可拆装底座

Three Phase, TEFC, UNIMOUNT[®]

- 1/4 HP through 30 HP
- 3600, 1800, 1200 and 900 RPM
- 56 through 286 frame
- Energy and NEMA Premium[®]† efficient
- C-face, footed and footless and removable base



通用用途工业马达 General Purpose Industrial Motors

三相, 敞开防滴型

1/4 HP~400 HP

3600, 1800, 1200, 900 RPM

机座尺寸: 48~449

节能型, NEMA Premium 高效节能型

Three Phase, ODP

- 1/4 HP through 400 HP
- 3600, 1800, 1200 and 900 RPM
- 48 through 449 frame
- Energy and NEMA Premium®† efficient



**NEMA
Premium**

C-Face机盖, 敞开防滴型, 全闭外扇型, 危险场所用

单相, 分相及电容起动

三相, 带安装脚或不带

1/12 HP~60 HP

3600, 1800, 1200 RPM

机座尺寸: 56~326

标准型, 节能型及高效节能型

C-Face: ODP, TEFC and Hazardous Location

- Single Phase, Split Phase and Capacitor Start
- Three Phase, footed and footless options
- 1/12 HP through 60 HP
- 3600, 1800 and 1200 RPM
- 56 through 326 frame
- Standard, Energy and Premium Efficient



**NEMA
Premium**

单相, 分相, 敞开防滴型及全闭外扇型

1/12 HP~3/4 HP

3600, 1800, 1200, 900 RPM

机座尺寸: 48~56

刚性焊接及托架安装座

可选单速或双速

C-Face机盖, 带安装脚或不带

可选手动或自动过热保护功能

Single Phase, Split Phase, ODP and TEFC

- 1/12 HP through 3/4 HP
- 3600, 1800, 1200 and 900 RPM
- 48 through 56 frame
- Rigid welded and cradle bases
- Single and two speed options
- C-face footed and footless
- Automatic or manual reset thermal overload protector options



单相, 电容起动, 敞开防滴型 及全闭外扇型

1/8 HP~10 HP

3600, 1800, 1200 RPM

机座尺寸: 48~215

刚性焊接及托架安装座

C-Face机盖, 带安装脚或不带

可选手动或自动过热保护功能

Single Phase, Capacitor Start, ODP and TEFC

- 1/8 HP through 10 HP
- 3600, 1800 and 1200 RPM
- 48 through 215 frame
- Rigid welded and cradle bases
- C-face footed and footless
- Automatic or manual reset thermal overload protector options



TITAN® 卧式

三相, 敞开防滴型, 防潮型, 全闭外扇型
危险场所用

150HP~4000HP

3600, 1800, 1200, 900, 720, 600 RPM

机座尺寸: 449~9608

电压: 460~6600V

滚珠轴承及套筒轴承

Titan® Horizontal

- Three phase, ODP, WPI, WP11, TEFC and Hazardous Location
- 150 HP through 4000 HP
- 3600, 1800, 1200, 900, 720 and 600 RPM
- 449 through 9608 frame
- 460 through 6600 volts
- Ball or sleeve bearings available



特定用途马达

Definite Purpose Motors

矢量马达

三相,全闭及全闭强制风冷型
1HP~15HP(全闭型)
1HP~300HP(强制风冷型)
机座尺寸:143~449
0~1800 RPM
保持定扭矩至接近0转速
使用变频电源时3年有限
产品保证

Vector Duty

- Three phase, TENV and TEBC
- 1 HP through 15 HP (TENV)
- 1 HP through 300 HP (TEBC)
- 143 through 449 frame
- 0-1800 RPM
- Constant torque near zero RPM
- Three-year limited warranty on inverter power*



变频马达

三相,敞开防滴及全闭外扇型
1HP~200HP
3600, 1800, 1200 RPM
机座尺寸:143~447
符合NEMA MG1Part 31变频要求

Inverter Duty

- Three phase, ODP and TEFC
- 1 HP through 200 HP
- 3600, 1800 and 1200 RPM
- 143 through 447 frame
- Meets NEMA® MG1 Part 31 requirements for inverter duty



热水循环泵

单相及三相,敞开防滴型
1/12HP~1-1/2HP
1800 RPM
机座尺寸:48、56
可直接替换B&G(Bell&Gossett),
Taco及Thrush品牌的循环泵的
马达

Hot Water Circulator Pump

- Single and three phase, ODP
- 1/12 HP through 1-1/2 HP
- 1800 RPM
- 48 and 56 frame
- Direct replacement motor for B&G® (Bell & Gossett), Taco® and Thrush™ brand circulator pumps



碳酸泵

单相,敞开防滴型
1/4HP~1/2HP
1800 RPM
机座尺寸:48

Carbonator Pump

- Single phase, ODP
- 1/4 HP through 1/2 HP
- 1800 RPM
- 48 frame



空压机

单相,敞开防滴
1/2HP~5HP
3600 RPM
机座尺寸:56, 143, 184
高停转扭矩

Air Compressor

- Single phase, ODP
- 1/2 HP through 5 HP
- 3600 RPM
- 56, 143 and 184 frame
- High breakdown torque



特定用途马达

Definite Purpose Motors

匠门及门用马达

单相及三相, 敞开防滴或全闭外扇型
1/3HP~1HP
1800 RPM
机座尺寸: 56, 56C

Gate and Door Motors

- Single and Three phase, ODP and TEFC
- 1/3 HP through 1 HP
- 1800 RPM
- 56 and 56C frames



制动马达

三相, 全闭外扇带制动器
1/3HP~20HP
1800, 1200 RPM
机座尺寸: 56~256
刚性机座, C-Face机盖
带安装脚或不带

Brake Motor

- Three Phase, TEFC with Brake Added
- 1/3 HP through 20 HP
- 1800 and 1200 RPM
- 56 through 256 frame
- Rigid base, C-face, footed and footless



农业用马达

单相及三相, 全闭外扇型
1/8HP~10HP
3600, 1800 RPM
机座尺寸: 56~1800
高扭矩或超高扭矩

Farm Duty

- Single and three phase, TEFC
- 1/8 HP through 10 HP
- 3600 and 1800 RPM
- 56 through 215 frame
- High torque or extra high torque



汽车行业, U型机壳

三相, 全闭外扇型
1/4HP~300HP
3600, 1800, 1200, 900 RPM
机座尺寸: 56~5008
符合General Motors GM-7EQ & GM-7EH, Ford EM1, 及Chrysler NPEM-105的规格

Automotive Duty, U-frame

- Three phase, TEFC
- 1/4 HP through 300 HP
- 3600, 1800, 1200 and 900 RPM
- 56 through 5008 frame
- Meets General Motors®† GM-7EQ & GM-7EH, Ford®† EM1, and Chrysler®† NPEM-105 spec



**NEMA
Premium**

消防水泵马达

三相, 敞开防滴
7-1/2HP~250HP
3600, 1800 RPM
机座尺寸: 184~445
消防水泵用途的UL认证品
可用于卧式机身和立式JP直连泵

Fire Pump Motor

- Three phase, ODP
- 7-1/2 HP through 250 HP
- 3600 and 1800 RPM
- 184 through 445 frame
- UL®† listed for fire pump application
- Available in horizontal frame and vertical JP close couple pumps



特定用途马达

Definite Purpose Motors

商用或民用水泵系统

单相及三相, 敞开防滴及
全闭外扇型
1/3HP~3HP
3600と1800 RPM
机座尺寸: 48, 56
C-Face, 方形法兰盘机盖
带安装脚或不带

Commercial and Residential Water System Pumps

- Single and three phase, ODP and TEFC
- 1/3 HP through 3 HP
- 3600 and 1800 RPM
- 48 and 56 frame
- C-Face, square flange
- Footed and footless



游池或浴池马达

单相及三相, 敞开防滴型
1/2HP~5HP
3600 RPM
机座尺寸: 48, 56
长螺栓, C-Face及方型法兰盘机盖
设计符合UL1081, 1795と1563

Pool and Spa Motor

- Single and three phase, ODP
- 1/2 HP through 5 HP
- 3600 RPM
- 48 and 56 frame
- Thru-bolt, c-face and square flange
- UL®† 1081, 1795 and 1563 design



ECOTECH EZ™ 系列变速马达及控制器

6.5"机壳外径, 56J C-Face机盖
或56Y方型法兰盘机壳
3HP, 可变转速, J目录
防冻传感器
全集成马达控制器

ECOTECH EZ™ Variable Speed Motor and Control

- 6.5" Frame Diameter; 56J C-Face or 56Y Square Flange frame
- 3 HP, Variable RPM; Category J
- Freeze Sensor
- Fully integrated motor control



2EZ™ 系列快速马达及控制器

6.5"机壳外径, 56J C-Face机盖
或方型法兰盘机壳
3/4~2 HP; 3450/1725 RPM
防冻传感器
全集成马达控制器

2EZ™ Speed Motor and Control

- 6.5" Frame Diameter; 56J C-Face or Square Flange
- 3/4 to 2 HP; 3450/1725 RPM
- Freeze Sensor
- Fully integrated motor control



暖通空调马达 HVAC Product Line Overview

MOJAVE®系列冷凝器风扇

单速或双速
1/4 HP ~ 3/4 HP
套筒轴承
70°C环境温度设计

MOJAVE® Series Condenser Fans

- 1 and 2 Speeds
- 1/4 HP through 3/4 HP
- Sleeve Bearings
- 70° Ambient Design



RESCUE®系列马达

多种不同HP应用的代替产品
燃气或电力熔炉

1/2 - 1/6 HP, 或是 3/4-1/5 HP
1075 RPM, 48机壳

冷凝器风扇马达

1/3 - 1/6 HP, 或是1/2-1/5 HP
1075 RPM, 机座尺寸48

RESCUE® Motors

• Replaces a variety of different HP applications

Gas or Electric Furnace motors

- 1/2 to 1/6 HP or 3/4 to 1/5 HP
- 1075 RPM, 48 Frame

Condenser Fan Motors

- 1/3 to 1/6 HP or 1/2 to 1/5 HP
- 1075 RPM, 48 Frame



冷凝器风扇

单相或三相,开放或全闭型

1/10 HP~2HP

1725, 1625, 1550, 1075, 825 RPM

机座尺寸: 48、56

单速或双速

Condenser Fans

• Single and three phase, OAO and TEAO

• 1/10 HP through 2 HP

• 1725, 1625, 1550, 1075 and 825 RPM

• 48 and 56 frame

• Single and two speed



风扇及鼓风机

单相,开放及全闭型

1/6 HP~1-1/2HP

3450, 1725, 1075, 825 RPM

单速,双速,3速或4速

皮带轮或直连驱动

Fan and Blower

• Single phase, ODP, OAO and TEAO

• 1/6 HP through 1-1/2 HP

• 3450, 1725, 1075 and 825 RPM

• Single, two, three and four speed

• Belt drive and direct drive



蒸发冷却器

单相,撇开防滴型

1/3 HP~1HP

1725 RPM

机座尺寸: 56

单速或双速

防锈转子铁心及传动组件

Evaporative Cooler

• Single phase, ODP

• 1/3 HP through 1 HP

• 1725 RPM

• 56 frame

• Single and two speed

• Corrosion resistant rotor core and actuator assembly



加热装置

单相,全闭型

1/15 HP~3/4HP

1550 and 1075 RPM

机座尺寸: 48、56

托架及螺栓安装

Unit Heater

• Single phase, TEAO

• 1/15 HP through 3/4 HP

• 1550 and 1075 RPM

• 48 and 56 frame

• Cradle and stud mount



暖通空调马达 HVAC Product Line Overview

空气循环马达

单相、开放或封闭式
1/4HP~1/2 HP
1800,1200,1100,1075,900 RPM
机座尺寸:48
可选取单速或双速
不震动

Air Circulator Motors

- Single Phase, OAO and TEAO
- 1/4 through 1/2 HP
- 1800, 1200, 1100, 1075 and 900 RPM
- 48 Frame
- Single and two speed options
- Non-oscillating



室内空调器

单相,开放或封闭式
1/10HP~3/4 HP
1725 及 1075 RPM
机座尺寸:42、48
单速,双速,3速及4速
自动重启热保护器

Room Air Conditioners

- Single phase, OAO and TEAO
- 1/10 HP through 3/4 HP
- 1725 and 1075 RPM
- 42 and 48 frame
- Single, two, three, four and five speed
- Automatic reset thermal overload protector



终端A/C热泵

单相、开放式
1/30HP~3/4 HP
1625, 1050, 1100, 925 RPM
直径5.0"、5.6"、6.3"
单速,双速,3速或4速

Package Terminal A/C Heat Pump

- Single phase, OAO
- 1/30 HP through 3/4 HP
- 1625, 1050, 1100 and 925 RPM
- 5.0", 5.6" and 6.3" diameter
- Single, two, three and four speed



燃油器

单相、全闭外扇型(安装时)
1/8HP~1HP
3450及1725 RPM
机座尺寸:48、56
可直接和Beckett, Carlin, Ducane和
Wayne Home Oil Burner
Systems进行代替

Oil Burner

- Single phase, Totally enclosed when mounted
- 1/8 HP through 1 HP
- 3450 and 1725 RPM
- 48 and 56 frame
- Direct OEM replacement for Beckett,®†
Carlin,®†
Ducane®† and Wayne®† Home Oil Burner
Systems



PEP®系列高效冷凝器风扇马达

能效值76%的单相电容运行马达
1075及825 RPM时可达1/2 HP
机座尺寸48,全闭空冷,滚珠轴承
70°C/158° F绝缘, 50/60 Hz额定值

PEP® High Efficiency Condenser Fan Motor

- 76% efficient Single Phase PSC
- Up to 1/2 HP in 1075 & 825 RPM
- 48 Frame, TEAO, Ball Bearing
- 70° C/158° F, 50/60 Hz Rated



RESCUE® EcoTech高效 直连驱动鼓风机

可直接代替商用及民用换气设备
及熔炉的直连驱动PSC马达
1/4 HP~1 HP
1075 RPM, 48机壳

RESCUE® EcoTech High Efficiency Direct Drive Blower

- Drop in replacement for PSC Direct Drive.
Commercial and Residential Air Handlers
and Furnaces
- 1/4 HP through 1 HP
- 1075 RPM, 48 Frame



暖通空调马达 HVAC Product Line Overview

RESCUE® 3.3 制冷蒸发器马达
开放式及全闭风冷型
两组接线供OEM厂商连接
可反转,减少在库库存单位

RESCUE® 3.3 Refrigeration Evaporator Motors

- OAO and TEAO
- Dual cord for OEM connection
- Reversible PSC designs
- Reversibility reduces SKUs to stock



特殊用途产品 Special Purpose Products

立式水泵马达

三相、WPI, WPIL, 全闭外扇型
危险场所
3HP~4000HP
3600, 1800, 1200, 900,
720, 600, 514 RPM
机座尺寸: 182~6810
可设计为高或普通推力
可使用立式中空轴及立式实心轴

Vertical Pump Motors

- Three phase, WPI, WPIL, TEFC and Hazardous Location
- 3 HP through 4000 HP
- 3600, 1800, 1200, 900, 720, 600 and 514 RPM
- 182 through 6810 frame
- Designed for high or normal thrust
- Available in vertical hollow shaft and vertical solid shaft



直连驱动水泵

单相及三相,敞开及全闭外扇型
危险场所
1HP~60HP
3600, 1800 RPM
机座尺寸: 143~326
可使用JM及JP规格轴
节能型

Close Coupled Pump

- Single and three phase, ODP, TEFC and Hazardous Location
- 1 HP through 60 HP
- 3600 and 1800 RPM
- 143 through 326 frame
- JM and JP shafts available
- Energy Efficient



电梯用

单相及三相
水中或空压
3HP~75HP
3600, 1800, 1200 RPM
机座尺寸: 71~315
Z及L32法兰盘安装

Elevator Duty

- Single and three phase
- Submersible and dry hydraulic
- 3 HP through 75 HP
- 3600, 1800 and 1200 RPM
- Z and L32 flange mounting



冷却塔

三相,全闭外扇型,全闭空冷型
2HP~100HP
1800, 1200, 1800/900,
1200/600 RPM
机座尺寸: 145~447
单速或双速
NEMA Premium高效率/变频
可替换Baltimore Aircoil Company,
Evapco,和SPX Cooling Technologies
(Marley)公司的产品

Cooling Tower

- Three phase, TEFC and TEAO
- 2 HP through 100 HP
- 1800, 1200, 1800/900 and 1200/600 RPM
- 145 through 447 frame
- Single speed and two speed
- NEMA Premium®†/inverter duty
- Replacement for Baltimore Aircoil Company, ®† Evapco®† and SPX Cooling Technologies (Marley®†)



有涂装可冲洗马达

单相及三相,全闭外扇型
1/2HP~10HP
3450, 1725, 1150 RPM
机座尺寸:56~215
脚安装,C-Face机盖带脚或不带
符合EISA标准

Painted Washdown

- Single and three phase, TEFC
- 1/2 HP through 10 HP
- 3450, 1725 and 1150 RPM
- 56 through 215 frame
- Foot mounted, c-face footed and footless
- Compliant with EISA Standards



无涂装可冲洗马达

三相,全闭强制风冷型
1/2HP~10HP
1725 RPM
机座尺寸:56HC~145TC
采用Inpro/Seal的VBX®轴支架
变频马达
符合EISA标准

Paint Free Washdown

- Three phase, TENV
- 1/2 HP through 10 HP
- 1725 RPM
- 56HC through 145TC frame
- VBX® bearing isolators by Inpro/Seal®
- Inverter Duty
- Compliant with EISA Standards



不锈钢可冲洗马达

三相,全闭强制风冷或外扇型
1/2HP~2HP
1725 RPM
机座尺寸:56HC~145TC
全不锈钢结构
转子及定子上涂有防锈剂
符合EISA标准

Stainless Steel Washdown

- Three phase, TENV and TEFC
- 1/2 HP through 2 HP
- 1750 RPM
- 56HC through 145TC frame
- All stainless steel construction
- Rust inhibitor on stator and rotor
- Compliant with EISA Standards



Varidyne® 2变频控制器

电子调节变频控制器
1HP~200HP(0.75-132 kW)
开环矢量控制:速度及扭矩
3k Hz – 18k Hz 开关频率范围
IP20 NEMA-1 外壳

Varidyne® 2 Variable Frequency Drive

- Electrical adjustable frequency drive
- 1 to 200 HP (0.75 to 132 kW)
- Open Loop Vector Control: Speed or Torque
- 3k Hz to 18k Hz Switching Frequency Range
- IP20 NEMA-1 Enclosure



All high performance motors carry a nameplate including a NEMA Premium®† trademark and European IE efficiency marks, providing a clear means for both users and OEM's to determine global regulatory compliance for their application. In addition to a full line of horizontal motors, the U.S. Motors® line of vertical motors will be available at premium efficiency levels to address customer requirements.

U.S. Motors® is a registered trademark of Nidec Motor Corporation. For more information about the U.S. Motors brand visit www.nidec-motor.com

所有带有NEMA Premium®商标及欧洲IE能效标志铭牌的高性能马达向用户及OEM制造商提供了符合全球规范的明确的解决方案。除全系列的卧式马达外，高效节能型U.S. Motors®立式马达也即将投入市场及满足客户的需求。

U.S. Motors是Nidec Motor Corporation的登录商标。关于U.S. Motors品牌的详细资料请您访问 www.nidec-motor.com

The U.S. Motors® brand NEMA Premium®† line of high performance commercial and industrial motors is designed to industry reduce energy consumption and comply with EISA regulations. This line features upgraded open dripproof and totally enclosed motors that meet or exceed NEMA Premium®† requirements.

U.S. Motors®品牌的NEMA Premium®商业及工业用马达是为了减少工业能源消耗及符合EISA法规而设计。产品通过提升敞开防滴或全闭型马达性能以达到或超过了NEMA Premium®高能效要求。

製造

NIDEC MOTOR CORPORATION

8050 W. Florissant Avenue | St. Louis, MO 63136

Phone: 888-637-7333 | Fax: 314-553-2087

FLB/2011 4/11 www.nidec-motor.com | www.usmotors.com

联系地址

 **Nidec** →All for dreams

日本電産テクノモータHD株式会社

東京営業部

〒141-0032 東京都品川区大崎1丁目20-13 日本電産東京ビル6F

TEL(03)5434-5731 FAX(03)5434-5733

大阪営業部

〒530-0004 大阪府大阪市北区堂島浜1-4-4 アクア堂島東館13F

TEL(06)6346-0551 FAX(06)6346-0553

名古屋営業部

〒451-0045 愛知県名古屋市西区名駅2丁目22-9 ニッセイ同和損保名古屋ビル6F

TEL(052)586-8741 FAX(052)586-8742

九州営業部

〒812-0016 福岡県福岡市博多区博多駅前4丁目1-1 日本生命博多駅前第2ビル3F

TEL(092)475-1073 FAX(092)475-1074

备忘: